

Technical Data Sheet

Divinol Bike Pro 4T 10W-60

Product description

Divinol Bike Pro 4T 10W-60 is a modern, synthetic multipurpose engine oil especially for motorbikes or quads with JASO MA2 which reduces sludge due to special hydrocrack-raffinates. High alkaline reserves guarantee good corrosion protection. The new formulation saves fuel and reduces oil consumption. A multipurpose oil for every season, can also be deployed for racing sport issues.

Specification

API SL/CF; JASO MA2

Characteristics

SAE Grade:	10W60
Ash / Sulfate DIN 51575:	0.9 %
Colour / DIN ISO 2049:	5
Viscosity/40°C / ASTM D 7042:	164 mm ² /s
Viscosity/100°C / ASTM D 7042:	23 mm ² /s
Viscosity index / ASTM D 2270:	170
Density/15°C / DIN EN ISO 12185:	0.860 g/cm ³
Pour point / DIN ISO 3016:	-39 °C
Flash point (Cleveland) / DIN EN ISO 2592:	220 °C
TBN:	8.2 mgKOH/g

Application

Racing sport motor oil for two-wheeled vehicles or quads.

49391

02/2018-49391-2

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1